

SIGN STANDARD

TRAFFIC CONTROL SIGNS FOR CONSTRUCTION PROJECTS

All traffic control signs shall conform to the current State of California, UNIFORM SIGN CHART. (The minimum-sized sign is allowed.)

Sign Blank: Blank material shall be made of either aluminum, steel or high density plywood.

△ Sign Color: All sign colors shall be reflectorized, conforming to the following requirements:

△ Yellow & Orange Signs: Reflective sheeting material shall be used for background color. Legend color shall be black and affixed to sheeting material either through the process of silk screening or non-reflective cut-out letters, symbols and borders.

Silver Signs: Reflective silver (white) sheeting material shall be used for background color. Legend color shall be black and affixed to background as described above for yellow signs.

Red Signs: Reflective red sheeting material shall be used for background color if reflectorized silver (white) cut-out letter and borders are utilized. Silver (white) reflective sheeting shall be used for silk screening in which the process will be reversed to produce a red background with silver (white) legend.

Black Signs: Non-reflective black background color. Legend color shall be reflective silver (white) and affixed to background either through the process of silk screening or reflective cut-out letters, numbers, symbols and borders. Non-reflective borders may be used only if sign is larger than 4' x 5' or (20 sq. ft.).

Green Signs: Non-reflective green background. Legend color shall be reflective silver (white) and affixed to background as described above for black signs.

Legend: Letters, numbers, symbols, borders, size and stroke shall conform to the State of California, Caltrans, standard sign lay-out specifications.

THE CONTRACTOR MUST OBTAIN WRITTEN APPROVAL FROM THE TRAFFIC ENGINEER PRIOR TO VARIANCES FROM THE ABOVE STANDARDS.

△ Revised 5/16/73 *ADD*
△ REVISED 6-6-77

Approved by *[Signature]*
City Traffic Engineer

Date: 5/18/76

CONSTRUCTION SIGNS

PARKING & TRAFFIC DIV., CITY OF RIV, CALIF

STANDARD DRWG. NO. 658